






# D08 - 2D/3D/4D

## Flow Readout Boxes D08 Series

### Features

D08 series Flow Readout Boxes provide a power supply for up to 4 Mass Flow Controllers or Mass Flow Meters and allow the user to set and display the flow for each controller or meter.

- High accuracy power supply
- CE mark compliant
- Ten years of production experience

	Type D08 - 2D	Type D08 - 3D	Type D08 - 4D
Flow readout boxes			
Description	Two-channel readout	Three-channel readout	Four-channel readout
Display type	3 ½ digital red LED		
Number of channels	2	3	4
Power supply	220 VAC ± 10% – 50Hz		
Maximum power consumption	18 W	25 W	45 W
Minimum load impedance	1 KOhms		
Inputs from MFC & MFM	2 x 0–5 VDC	3 x 0–5 VDC	4 x 0–5 VDC
Output power supply	+ 15 V ± 5%, 300 mA – 15 V ± 5%, 600 mA	+ 15 V ± 5%, 600 mA – 15 V ± 5%, 1.2 A	+ 15 V ± 5%, 600 mA – 15 V ± 5%, 1.2 A
Output to MFC & MFM	2 x 0–5 VDC	3 x 0–5 VDC	4 x 0–5 VDC
Dimensions (L x H x D)	440 x 100 x 220 mm		
Weight	4.2 Kg	4.3 Kg	4.4 Kg

· For information not included in this datasheet, please contact Qualiflow sales representative.