



D-Series Diaphragm Shut-Off Valve

Part Number Description

D [a] [b , b] [r] [s] - [TR] - [1 , 2 , 3 , 4]

[a] - Actuator Type

- [Q] Manual ¼ Turn
- [T] Manual Toggle
- [O] Pneumatic Normally Open
- [C] Pneumatic Normally Closed

[b] - Body Configuration

See next page for body configuration chart.
Other configurations available upon request.

[r] - Flow Range

- [S] Standard flow (Cv = 0.24)

[s] - Surface Finish

- [Q] Q+ Process Electropolished Ra0.15µm (6µin)

[TR] - Temperature Range

- [_] Standard Temperature (leave blank)
- [MT] Middle Temperature (180°C)

[1,2,3,4] - Fitting Type

See next page for fittings configuration and specify :

- [1,2] 2-way valve
- [1,2,3] 3-way valve
- [1,2,3,4] 4-way valve

Fitting list :

- [F] ¼" VCR Female
- [M] ¼" VCR Male
- [C] Swagelok ¼"
- [G] Swagelok 6mm
- [W] Welded butt ends

On request, specify your surface mounting :

- [SC] C-Seal (2 ways)
- [SC1"1/8] C-Seal 1"1/8 (2 ways)

D-Series Diaphragm Shut-Off Valve

Body Configuration Chart

Config. Nb	Valve close	Valve open	Schematic	Fittings configuration for ordering
21				
22				
23				
31				
32				
33				
34				
35				
36				
41				
42				
43				
44				

Greyed-out fields show **special valve configuration**